This document is hosted by Old Will Knott Scales www.oldwillknottscales.com WBW-M Series Approved Wash Down Scales





Ideal for food preparation, food processing plants, agricultural facilities and more, WBW-M series scales feature an IP66-rated wash down housing and a large stainless steel weighing pan. Color indicators for under, okay and over limits make check weighing fast and easy.



With nearly 40 years of experience in the production of scales and balances, Adam Equipment provides excellent value in products and service to achieve the best possible customer satisfaction.













WBW-M Highlights:

Check weighing product is faster than ever with the WBW-M's color-coded LED indicators. Amber, green and red LEDs quickly show you if a sample is within acceptable limits, over, or under without looking at the actual weight.

An easy-to-read backlit LCD with capacity tracker shows capacity usage as well as the weight. The capacity tracker helps prevent users from exceeding the scale's capacity when adding ingredients or making up batches.

WBW-M scales can be moved to where they are needed, thanks to the internal rechargeable battery pack. And the vertical front panel makes them easy to read and operate on a counter, table or bench.

IP66 for wash down environments with extensive sealing both inside and out give the ultimate in protection for those wet applications. Advanced overload protection helps protect the scale from overloads.


WBW-M...designed for food, agriculture, and other wash down applications.


Features

- IP66-rated for wash down
- Backlit LCD with capacity tracker
- Colored LED check limit indicators
- Rechargeable battery and AC adapter included
- Stainless steel pan
- Weighs in pounds, ounces, pound / ounces, grams, kilograms
- Overload protection
- NTEP and Measurement Canada Approved

Applications

- Weighing
- Check weighing









Colored LEL indicators

Technical Specifications

Model	WBW 6aM	WBW 15aM	WBW 30aM	WBW 6aM-KG	WBW 15aM-KG	WBW 30aM-KG
Capacity	6lb	15lb	30lb	3000g	6000g	15kg
Readability	0.002lb	0.005lb	0.01lb	1g	2g	5g
Repeatability (S.D.)	0.002lb	0.005lb	0.01lb	1g	2g	5g
Linearity (+/-)	0.004lb	0.01lb	0.02lb	2g	4g	10g
Pan Size	8.3" x 6.8"					
Weighing Units	lb, oz, g, kg					
Applications	Weighing, check weighing					
Stabilization Time	2 seconds typical					
Calibration	Automatic External					
Display	6 digits backlit LCD digital display					
Power Supply	AC adapter, internal rechargeable battery (both included)					
Operating Temperature	14° to 104°F					
Housing	IP66 (only when used on battery) sealed ABS plastic housing with stainless steel pan					
Overall Dimensions (wxdxh)	9.1"x 10.4"x 6"					
Net Weight	7.3lb					

