







Compact Scale **HL Series**







- **High Resolution**(HL-100–10,000d_d; HL-400/4000–4,000d_d; HL-200/2000–2,000d_d
- Solid & Reliable Design
- Large Square Weighing Pan (except HL-100)
- Detachable Weighing Pan (except HL-100)
- Clear LCD Display (8mm)
- Accurate Reading in Wide Temperature Range
- Portable (6 "AA" batteries, not included)
- Stability Indicator
- Low Battery Indicator
- Separate Keys for Power & Re-Zero
- Auto Power Off
- Standard Carrying Case (HL-100 only)
- AC Adapter (option)



Specifications

MODEL	HL-100				
Capacity/Resolution	100 x 0.01g 3.5oz x 0.0005oz 500ct x 0.05ct				
Linearity	0.03g				
Repeatability/Std. Dev.	0.02g				
Pan Size	φ 70mm				
Battery Life (Approximately)	140 hours with alkaline type cells (70 hours with manganese type cells)				
Weight (Approximately)	500g				

MODEL	HL-200	HL-400	HL-2000	HL-4000		
Capacity/Resolution	200 x 0.1g	400 x 0.1g	2000 x 1g	4000 x 1g		
Linearity	0.2g	0.4g	2g	4g		
Repeatability/Std. Dev.	0.1 g	0.2g	1g	2g		
Pan Size	136(W) x 136(D) mm					
Battery Life (Approximately)	200 hours with alkaline type cells (100 hours with manganese type cells)					
Weight (Approximately)	500g					

Specifications subject to change without notice.

Specifications Common for HL series

Display Liquid Crystal Display, 8mm height $-10 \text{ C} \sim 40 \text{ C}/14 \text{ F} \sim 104 \text{ F RH less than } 85\%$ Operating Temp. 6 x R6P/LR6/"AA" size batteries or AC adapter (option) Power

Recommended Calibration Mass

HL-100 AD-1700-50G Calibration Weight, 50g AD-1700-100G Calibration Weight, 100g HL-200 AD-1700-200G Calibration Weight, 200g HL-400 AD-1700-400G Calibration Weight, 400g HL-2000 AD-1700-2KG Calibration Weight, 2000g HL-4000 AD-1700-4KG Calibration Weight, 4000g

Options AX:3001848 Stainless Steel Platform Cover

(HL-400/2000/4000 only)

Accessories FV-05 AC Adapter (110V)

FV-05L AC Adatper "L" Jack (110VAC)

FV-06 AC Adatper (220VAC)

