

### Intelligent-Weigh™ Stainless Steel Washdown Bench Scale



- NTEP Approved
- Stainless Steel, Washdown – NEMA 4X / IP 67 Protection
- Bi-directional RS 232 Interface
- Heavy Duty Construction
- AC/DC Adapter and Rechargeable Battery
- Easy Setup and Configuration

#### With Intelligent-Weigh™ Indicator


 Class III


  



 

#### With Intelligent-Check™ Indicator

 Class III



Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance



Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance

IWT / ICT

Series

Model	IWT-150-18	IWT-300-18	IWT-500-18	IWT-150-24	IWT-300-24	IWT-500-24
Capacity	150 lb / 75 kg	300 lb / 150 kg	500 lb / 250 kg	150 lb / 75 kg	300 lb / 150 kg	500 lb / 250 kg
Readability	0.05 lb / 0.02 kg	0.1 lb / 0.05 kg	0.1 lb / 0.05 kg	0.05 lb / 0.02 kg	0.1 lb / 0.05 kg	0.1 lb / 0.05 kg
Divisions	3,000		50,00	3,000		5,000
Weighing Units	NTEP; lb, kg only / Non-NTEP Primary units – kg, lb,oz (Gn, dwt, ct, lb:oz also available)					
Functions	Net/gross, pre-tare function, checkweighing (parts counting, animal hold, peak hold non-NTEP)					
Tare Range	To capacity by subtraction					
Power Source	Built-in rechargeable battery or external power adapter (included)					
Construction	All stainless steel washdown with aluminum load cell					
Display	1 inch high backlit LCD display					
Platform Size (W x D x H)	18 x 18 x 6 inches / 457 x 457 x 152 mm			24 x 24 x 6 inches / 610 x 610 x 152 mm		
Overall Dimensions (W x D x H)	18 x 18 x 34 inches / 457 x 457 x 152 mm			24 x 24 x 34 inches / 610 x 610 x 152 mm		
Connectivity	RS 232 interface Bi-Directional or serial printer output					
Net Weight	48 lb / 22 kg			71 lb / 32.2 kg		
Shipping Weight	52 lb / 22.3 kg			88 lb / 40 kg		
NEMA / IP Rating	Platform: IP 66					
	Indicator: NEMA 4X / IP 67					
Approvals	Platform: NTEP CoC # 04-099					
	Indicator: NTEP CoC # 07-110, Measurement Canada Approval #AM-5651					
Options	Stainless Steel Wheel Kit, Printer					
Intelligent-Check™ Indicator Option	Graphic Checkweighing Display, Lot #, Time/Date, 3 Weighing Speeds, Pushbutton Tare					

Features	Benefits
Large backlit display	Can be easily read in less than ideal conditions
Adjustable weighing speed filters	Allows you to adjust for operational and environmental conditions
Automatic Zero tracking	Ensures that you always start weighing at zero
Built-in rechargeable battery or external power adapter	Portability (battery lasts approximately 120 hours)
Automatic power save	Conserves battery power
Low battery indicator	Alerts you to charge the battery, saving downtime
Gravitational correction software	Enables you to input different G acceleration factors
Hold function (non-NTEP model)	Both peak hold and hold functions are available to keep weight displayed while it is being recorded
RS 232 Interface	Allows for finer counting



Optional Intelligent-Check™ Indicator