

Setra Quick Count™



The extremely high accuracy inherent in Setra's proprietary variable capacitance ceramic load cell is now available in Quick Count, a moderately priced, easy to use counting scale.



- High Accuracy & Resolution
- Plug and Play
- Auto Zero Tracking
- Selectable Display Update Speed
- Two Year Warranty



Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance

Model	QC - 2.2	QC - 5.5	QC - 11	QC - 27	QC - 55	QC - 110
Capacity	2.2 lb (1 kg)	5.5 lb (2.5 kg)	11 lb (5 kg)	27 lb (12.5 kg)	55 lb (25 kg)	110 lb (50 kg)
Readability	0.0002 lb / 0.1 g	0.00005 lb / 0.02 g	0.0001 lb / 0.05 g	0.0005 lb / 0.2 g	0.001 lb / 0.5 g	0.002 lb / 1 g
Displayed Divisions	110,000	110,000	110,000	54,000	55,000	55,000
Platform Dimensions	5" diameter (130 mm)		6.25" diameter (160 mm)	11" x 13" (280mm x 330mm)		
Overall Dimensions	14" W x 15.5" D x 6" H (360 x 395 x 145 mm)					
Internal Counting Resolution	To 1 part in 500,000					
Counting Accuracy	Selectable from 95% to 99.99%					
Minimum Sample Size	Selectable from 1 to 999					
Display Update Rate	Selectable, up to 5 times per second					
Counting Capacity	999,999 pieces					
Memory	Up to 256 records including: part ID, count, average piece weight, tare					
Data Communication	Bidirectional RS232					
Selectable Baud Rates	300, 600, 1200, 2400, 4800, 9600					
Selectable Parity	Even/odd/none					
Display	6 digit LCD					
Pan	Stainless Steel					
Operating Temperatures	40° to 100° F (5° to 43° C)					
Power Adapter	Input - 110 VAC/60 Hz Output - 16.5 VDC @ 1000 ma					
Weighing Units / Functions	lb, g, oz, dwt, t oz, ct, gr					
Shipping Weight	27 lb (12 kg)	27 lb (12 kg)	31 lb (14 kg)	31 lb (14 kg)	31 lb (14 kg)	31 lb (14 kg)
Options	Rechareable Battery, DYMO Labelwriter SE 300 Printer & Setra 400 Direct thermal Printer, Setra 500 Barcode Scanner.					

Features	Benefits
Accuracy monitor	Enables the supervisor to select special settings that check the sampling process and, if necessary, cause the scale to prompt the operator if the number of pieces used in the sample is too small.
Programmable RS-232 output	With ScriptCoder™, allows up to 10 custom label designs with barcodes to be printed on a thermal label printer.
Bidirectional data communications	Allow piece weights and commands to be downloaded from a computer.
Serviceability	Thanks to a modular design, Quick Count scales can be serviced on-site by an Authorized Serta Service Technician.
Stability Indicator	Displays an 'OK' icon to confirm that the scale is stable and weight measurements are accurate.
Large LCD display	For quick and easy reading and increased productivity

Different Platform Sizes

