



Capacity 150kg x 0.1kg 330lb x 0.2lb



Thank you for purchasing the My Weigh® Titan™ bathroom scale. Please read all operating instructions carefully before use. This electronic scale is a precision instrument. With normal care and proper treatment, it will provide years of reliable service. For more information please visit www.myweigh.com

# **OPERATION INSTRUCTIONS**

## **Batteries**

Insert 3 AAA batteries into the battery compartment on the bottom (underside) of the scale. Be sure the polarity (+/-) is correct when installing batteries

### Weighing

Step onto the centre of the scale. The display will show "0.0 lb" (or 0.0 kg) and then your weight will be displayed when the reading is steady.

#### Dower of

The power will shut down automatically after no operation is detected for about 30 seconds.

#### Units

To change the units move the switch underneith the scale. It is possible to change between kg/lb/st

## IMPORTANT NOTES

- \*\*\* If the Scale ever malfunctions please try installing a new battery, sometimes a low battery or defective battery may cause inaccurate readings or other errors. \*\*\*
- If the display indicates "Lo " when the scale starts, it means the battery needs to be replaced.
- .- When over-loaded, "EEEE" will be displayed.
- Use the unit on hard, flat, dry and secure surface only.
- Place the unit in an area free from high temperature or high humidity. To clean, use dampened cloth and mild detergent.
- Avoid excessive impact or vibration to the unit.
- If you do not intend to use this unit for a long period of time, remove the battery before storage.
- Do not attempt to disassemble the unit, otherwise the warranty will become void.
- The scale is intended for home and personal use only (not legal for commerce).
- This scale must only be used on a hard surface such as tile, wood, or linoleum.
- This and most bath scales will not perform properly on thick-carpeted surfaces.
- If the display indicates "Lo " when the scale starts, it means the battery needs to be replaced.

Capacity	150kg x 0.1kg 330 b x 0.2 b	Units	kg, lb, st
Deviation		+/-1%	
Temperature range		Optimum 15-20°C	
Power source		3 x AAA alkaline batteries	









