

BE ADAM

Adam Equipment

CB Balance



CONTENTS

1.0 INTRODUCTION	1
2.0 KEY OPERATIONS	1
3.0 CALIBRATION	2
4.0 MODEL SPECIFICATIONS	2
WARRANTY INFORMATION	3
Auto-off addendum for newer models	6

1.0 INTRODUCTION

Each CB balance comes with 2 x AA batteries included. There is a choice of three capacities, each with three weighing units including grams, pounds and ounces, selectable by a Units key (grams only if the Mode key is not enabled). The bright backlit display enables operation in any degree of light, and the 304 grade stainless steel top pan offers protection against most materials and liquids. With easy calibration through the keypad the CB ensures correct and accurate weighing at all times.

Always position the balance on a steady and level surface before use. Use the levelling feet and bubble indicator to adjust the balance to level.

The display “EEEE” indicates that the balance has been overloaded or damaged.


The display “Lo” or flashing battery indicator symbol indicates that the batteries must be changed.

Remove the cover on the underside of the balance to fit new batteries.

2.0 KEY OPERATIONS



Power on/off key.



Weighing mode selection key (if enabled) – g, oz or lbs.



Zero key is used to zero the balance or remove the weight of an empty container.

3.0 CALIBRATION

To calibrate the balance follow the instructions below.

- I. Turn on the scale and zero it.
- II. Press and hold **【MODE】** and **【→0←】** keys together for about 5 seconds until the display shows internal codes value.
- III. Press **【MODE】** key once, the display will show CALL→[xxxx], (where xxxx is the full capacity weight value).
- IV. Load calibration weight as per the displayed value, and the scale will be automatically calibrated. After calibration, the scale will return to normal weighing mode. Calibration is now complete.

4.0 MODEL SPECIFICATIONS

Model	CB 501	CB 1001	CB 3000
Maximum Capacity	500g	1000g	3000g
Readability	0.1g	0.1g	1g
Units of Measure	grams (default), lbs and oz if the mode key is enabled		
Operating Temperature	0 - 40 degrees C		
Power Supply	2 x AA batteries or 6v DC 200ma Adaptor		
Calibration Mass	500g	1000g	3000g
Display	5 x 12mm/0.47 inches high digits		
Pan Size	130mm/5.1 inches diameter		
Overall Dimensions (w x d x h)	160 mm x 210mm x 65mm 6.3 in x 8.1 in x 2.6 in		
Net Weight	385 g / 0.85 lbs		

WARRANTY INFORMATION

Adam Equipment offers Limited Warranty (parts and labour) for the components failed due to defects in materials or workmanship. Warranty starts from the date of delivery.

During the warranty period, should any repairs be necessary, the purchaser must inform its supplier or Adam Equipment Company. The company or its authorised Technician reserves the right to repair or replace the components at any of its workshops depending on the severity of the problems. However, any freight involved in sending the faulty units or parts to the service centre should be borne by the purchaser.


The warranty will cease to operate if the equipment is not returned in the original packaging and with correct documentation for a claim to be processed. All claims are at the sole discretion of Adam Equipment.

This warranty does not cover equipment where defects or poor performance is due to misuse, accidental damage, exposure to radioactive or corrosive materials, negligence, faulty installation, unauthorized modifications or attempted repair or failure to observe the requirements and recommendations as given in this User Manual. Additionally rechargeable batteries (where supplied) are not covered under warranty.

Repairs carried out under the warranty does not extend the warranty period. Components removed during the warranty repairs become the company property.

The statutory right of the purchaser is not affected by this warranty. The terms of this warranty is governed by the UK law. For complete details on Warranty Information, see the terms and conditions of sale available on our web-site.

WEEE 2012/19/EU



This device may not be disposed of in domestic waste. This also applies to countries outside the EU, per their specific requirements. Disposal of batteries (if fitted) must conform to local laws and restrictions.

Cet appareil ne peut être éliminé avec les déchets ménagers. L'élimination de la batterie doit être effectuée conformément aux lois et restrictions locales.

Dieses Gerät nicht mit dem Hausmüll entsorgt.

Dispositivo no puede ser desechado junto con los residuos domésticos

Dispositivo non può essere smaltito nei rifiuti domestici.

FCC / IC CLASS A DIGITAL DEVICE EMC VERIFICATION STATEMENT

NOTE: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC rules and Canadian ICES-003/NMB-003 regulation. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

CALIFORNIA PROPOSITION 65 - MANDATORY STATEMENT

WARNING: This product includes a sealed lead-acid battery which contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



Adam Equipment products have been tested with, and are always supplied with mains power adaptors which meet all legal requirements for the intended country or region of operation, including electrical safety, interference and energy efficiency. As we often update adaptor products to meet changing legislation it is not possible to refer to the exact model in this manual. Please contact us if you need specifications or safety information for your particular item. Do not attempt to connect or use an adaptor not supplied by us.

ADAM EQUIPMENT is an ISO 9001:2008 certified global company with more than 40 years' experience in the production and sale of electronic weighing equipment.

Adam products are predominantly designed for the Laboratory, Educational, Health and Fitness, Retail and Industrial Segments. The product range can be described as follows:

- Analytical and Precision Laboratory Balances
- Compact and Portable Balances
- High Capacity Balances
- Moisture analysers / balances
- Mechanical Scales
- Counting Scales
- Digital Weighing/Check-weighing Scales
- High performance Platform Scales
- Crane scales
- Mechanical and Digital Electronic Health and Fitness Scales
- Retail Scales for Price computing

For a complete listing of all Adam products visit our website at

www.adamequipment.com

<p>Adam Equipment Co. Ltd. Maidstone Road, Kingston Milton Keynes MK10 0BD UK Phone:+44 (0)1908 274545 Fax: +44 (0)1908 641339 e-mail: sales@adamequipment.co.uk</p>	<p>Adam Equipment Inc. 1, Fox Hollow Rd. 06478 USA Phone: +1 203 790 4774 Fax: +1 203 792 3406 e-mail: sales@adamequipment.com</p>	<p>AE Adam GmbH. Instenkamp 4 D-24242 Felde Germany Phone +49 (0)4340 40300 0 Fax: +49 (0)4340 40300 20 e-mail: sales@adamequipment.co.za</p>
<p>Adam Equipment S.A. (Pty) Ltd. 7 Megawatt Road, Spartan EXT 22 Kempton Park, Johannesburg, Republic of South Africa Phone +27 (0)11 974 9745 Fax: +27 (0)11 392 2587 e-mail: sales@adamequipment.co.za</p>	<p>Adam Equipment (S.E. ASIA) PTY Ltd 2/71 Tacoma Circuit CANNING VALE 6155 Perth Western Australia Phone: +61 (0) 8 6461 6236 Fax +61 (0) 8 9456 4462 e-mail: sales@adamequipment.com.au</p>	<p>Adam Equipment (Wuhan) Co. Ltd. A Building East Jianhua Private Industrial Park Zhuanyang Avenue Wuhan Economic & Technological Development Zone 430056 Wuhan P.R.China Phone: + 86 (27) 59420391 Fax + 86 (27) 59420388 e-mail: info@adamequipment.com.cn</p>

© Copyright by Adam Equipment Co. All rights reserved. No part of this publication may be reprinted or translated in any form or by any means without the prior permission of Adam Equipment.

Adam Equipment reserves the right to make changes to the technology, features, specifications and design of the equipment without notice.

All information contained within this publication is to the best of our knowledge timely, complete and accurate when issued. However, we are not responsible for misinterpretations which may result from the reading of this material.

The latest version of this publication can be found on our Website.

www.adamequipment.com

AUTO-OFF SETTINGS (Newer versions)

For newer versions of the CB the auto-off feature can be disabled.

Make sure the scale is off.

Press and hold the "Mode" key. The scale will power on in the settings mode.

Press the "Zero" key to cycle through the settings until you see "A---x" ("x" will be either 0, 1, 5, or 10. These numbers represent the number of minutes before the scale automatically turns off. "0" disables the auto-off feature.)

Press the "Mode" key to cycle through the options.

A---0 (Auto-off disabled)

A---1 (Auto-off after 1 minute of inactivity)

A---5 (Auto-off after 5 minutes of inactivity)

A---10 (Auto-off after 10 minutes of inactivity)