

Intelligent-WeighTM Heavy Duty Bench & Platform Scale



- Cast Aluminum Structure
- Strong Steel Pillar
- Stainless Steel Platform Cover
- Optional Wheel Kit Available
- 132 lb to 660 lb Range
- Platform Size 16.7" x 20.6"
- Rechargeable Battery
- 1" LCD Backlit Display
- lb / kg Keyboard Enabled
- Filter for Animal Weighing















AFW Carias

A Higher Level of Precision . . . A Higher Level of Performance

Model	AFW-F132	AFW-F330	AFW-F660
Capacity	132 lb / 60 kg	330 lb / 150 kg	660 lb / 300 kg
Readability	0.02 lb / 0.01 kg	0.05 lb / 0.02 kg	0.1 lb / 0.05 kg
Divisions	6,000	7,500	6,000
Weighing Units / Functions	lb / kg, animal weighing		
Stabilization Time	< 2 seconds		
Tare Range	To capacity by subtraction		
Power Source	Built-in rechargeable battery or external power adapter (included)		
Construction	Stainless steel platform with heavy duty aluminum structure		
Display	1 inch high, 7 segment, wide viewing angle backlit LCD display		
Platform Size (W x D x H)	16.7 x 20.6 x 4.5 inches / 425 x 524 x 115 mm		
Overall Dimensions (W x D x H)	16.7 x 29 x 35 inches / 425 x 737 x 889 mm		
Operating Environment	32 ° F to 104 ° F non condensing R.H. ≤ 95%		
Net Weight	39 lb / 17.7 kg		
Shipping Weight	47 lb / 21.3 kg		
Options	Dry Cell Battery Pack, Wheel Kit		

Features	Benefits	
Deep skirted stainless steel platter	Easy to clean for food processing or harsh environments	
Overload and shock protection	Will withstand harsh industrial environments	
Backlit LCD display with wide viewing angle	Easy to see weight values from a distance, reduces mistakes	
Reads in kilograms or pounds	Flexibility of operation	
Built-in rechargeable battery and external A/C adapter	Portability, minimum 150 hours	
Zero tracking	Ensures that you always start weighing from zero	
Automatic power save	Conserves battery power	
Low battery indicator & charge status light	Alerts you to charge the battery, saving downtime	
Adjustable feet & spirit level	Ensures scale can be leveled on uneven working surfaces	
In use dust cover for indicator	Keeps indicator clear from contamination	
Indicator rotates through 135 degrees	Enables viewing from all angles	
Wide angle LCD display	Can be seen from a wide viewing range in sunshine, ideal for outdoor use	
Options for display: platform, pillar or wall mounted (3 ft of cable supplied)	Flexibility of operation and position	
Optional auto tare function	Allows the first article on the platter to be automatically tared.	
Gravitational correction software	Enables you to input different G acceleration factors	