



150g	x0.05g
300g	x0.1g
600g	x0.2g
1500g	x0.5g
3000g	x0.5g
6000g	x1g
12kg	x0.002kg
30kg	x0.005kg



- . All Stainless Steel Washdown
- . Ideal Portion Weigher
- . Rechargeable Battery & Power Adapter
- . Reads In: g, lb, ounces
- . Heavy Duty
- . Low Profile



Optional



Model	AGS-300BL	AGS-600BL	AGS-1500BL	AGS-3000BL	AGS-6000BL	AGS-12KBL	AGS-30KBL
Capacity	150 g / 300 g 0.66 lb	300 g / 600 g 1.32 lb	600 g / 1500 g / 3.3 lb	3000 g / 6.6 lb	6000 g / 13.2 lb	12 kg / 26.4 lb	30 kg / 66 lb
Readability	0.05 g / 0.1 g 0.00002 lb (non-NTEP 0.01g)	0.1 g / 0.2 g 0.0005 lb (non-NTEP 0.02g)	0.2 g / 0.5 g 0.002 lb (non-NTEP 0.05g)	0.5 g / 0.002 lb (non-NTEP 0.1g)	1 g / 0.005 lb (non-NTEP 0.2g)	0.002 kg / 0.005 lb (non-NTEP 0.5g)	0.005 kg / 0.02 lb (non-NTEP 0.001kg)

Divisions	3,000	6,000
Weighing Units	g, lb, ounces	
Functions	Accumulation	
Stabilization Time	< 1.5 seconds	
Tare Range	To capacity by subtraction	
Power Source	Built-in rechargeable battery or external power adapter (included)	
Construction	Stainless steel pan and housing	
Display	0.75 inch / 19 mm wide viewing angle backlit LCD	
Pan Size (W x D)	5.75 inches / 146 mm diameter	8.25 x 8.25 inches / 210 x 210 mm
Dimensions (W x D x H)	9.1 x 12.2 x 3 inches / 230 x 310 x 75 mm	
Operating Environment	32° ~ 104° F non condensing R.H. ≤ 85%	
Net Weight	8.15 lb / 3.7 kg	
Shipping Weight	12.3 lb / 5.6 kg	
NEMA/IP Rating	IP 65	
Options	Carrying Case	
Approvals	NTEP C.o.C.# 18-130	

High resolution is only available in "normal" setting. Not NTEP approved.

Features	Benefits
All stainless steel housing and pan	Easy to clean for food processing or harsh environments
Heavy duty construction	Will withstand harsh industrial operation
Sealed electronics	Improved water and dust resistance
Low profile, compact size	Uses less counter space
Reads in grams, pounds, and ounces	Flexibility of operation
Built-in rechargeable battery or external power adapter	Portability – battery lasts a minimum of 150 hours (without backlight)
Accumulation function	Allows you to add together consecutive weights to arrive at a total
Zero tracking	Ensures that you always start weighing at zero
Automatic power save	Conserves battery power
Low battery indicator	Alerts you to charge the battery, saving downtime
Easy calibration function	Ensures accuracy
Adjustable stainless steel feet with rubber inserts	Scale remains level for accurate results on uneven working surfaces – anti-slip
Wide-angle LCD display with backlight	Can be seen from a wide viewing range