





Weighing Technology

A Higher Level of Precision . . . A Higher Level of Performance



AHS NTEP Series

Model	AHS-6	AHS-15	AHS-30	AHS-60
Capacity	6 lb / 2.7 kg	15 lb / 5 kg	30 lb / 13.6 kg	60 lb / 27 kg
Readability	0.005 lb / 2 g	0.01 lb / 5 g	0.02 lb / 0.01 kg	0.05 lb / 0.02 kg
Divisions	Varies. See C.o.C.			
Weighing Units / Functions	g (kg), lb			
Stabilization Time (seconds)	< 2			
Tare Range	To capacity by subtraction			
Safe overload	200% of rated capacity – ultimate overload 300%			
Power Source	4 size “C” type batteries (not included) or external power adapter (not included)			
Construction	ABS Plastic			
Display	1 in / 25.4 mm, 7 segment, wide viewing angle backlit LCD			
Pan Size (W x D)	Optional 12 inch diameter stainless steel hanging pan and cantilever beam			
Overall Dimensions (W x D x H)	4.72 x 2.25 x 7.25 in / 120 x 57 x 185 mm			
Operating Environment	14 °F to 104 °F non-condensing R.H. ≤ 85%			
Net Weight	1 lb / 1.5 kg			
Shipping Weight	2 lb / 0.9 kg			
Options	12” Diameter Stainless Steel Hanging Pan, AC/DC Power Adapter, Traveler™ Transport Case			
Approvals	NTEP C.o.C. #18-098			

Features	Benefits
Lightweight	Easy to use
Large display	Can be easily read in less than ideal conditions
Battery operation	Allows 250 hours of non-stop operation
Automatic power save	Conserves battery power
Hold function	Allows the last displayed weight to remain after the load is removed from the scale
Auto Zero tracking	Ensures that you always start weighing at zero

Optional Transport Case



Optional Hanging Pan

